TAG SPECIFICATIONS





UHF RFID TAG FOR LAUNDRY

- \checkmark Self adhesive can heat seal directly on Linen or Garments
- ✓ Frequency: 868 to 928 MHZ (Passive)
- ✓ Working Temperature up to 260 °C
- ✓ Working Pressure: up to 60 Bar
- ✓ Life Span: 300 Wash Cycles or 3 Years (T & C apply)
- ✓ Dimension : 20 x 70 x 1.5 mm
- ✓ Op Transponder Chip : ISO 18000 6C, EPC Class 1 Gen 2, 96 bit EPC memory
- ✓ Material : 100% Cotton Hot-melt adhesive backside
- ✓ Press Status : 12-15 secs at 205°C at 6 bars at Standard Thermal Transfer Press
- ✓ Reading distance : Up to 16 m Streamlined for 1.2 m with RealeX system Readers
- ✓ Wash proof, heavy industry laundry tag
- \checkmark Multi reading that allows accurate performance in metal trolleys. Up to 950 pcs.
- \checkmark Resistant to temperature. Ironing friendly including chest heated iron rollers
- ✓ Can be used in dry cleaning processes
- ✓ Performer 20 X 70 New registered design with enhanced performance Patent pending

🐼 Realex Solutions